



D-Series

LED Downlight Family

It's All About Common Sense Solutions, Making Lighting Simpler

NICOR's D-Series luminaires offer a comprehensive family of LED downlight fixtures that complement one another no matter your design space needs. From LED color rendering and trim finishes to fixture performance, the design style of each luminaire is consistent across all fixture types. You can now achieve a harmonious look regardless of your application needs. The D-Series LED luminaires are a perfect choice for commercial, retail, institutional, and residential applications. Upgrading to energy efficient LED lighting has never been easier or more stylishly affordable.

The NICOR Team







design improvement meets new industry standards like Title 24 and CEC making it an ideal and affordable solution.

Available in Black, Nickel, Oil-Rubbed Bronze and White Compatible with most 5" and 6" recessed housings (DLRS6 Only) Compatible with most 4" recessed housings (DLR4 Only) Suitable for use in IC Rated recessed housings 60,000 hour life expectancy Greater than 90 CRI with R9 greater than 60 Meets California Quality Specifications Easy installation with adjustable torsion springs (DLR56 Only) Easy installation with mounting clip system (DLR4 Only) Dimmable to 10% with most standard dimmers Durable construction with integrated trim













DLR4

DLR56 with Baffle



5 Year Warranty



The DLS4 and DLS56 from NICOR® are the perfect LED downlight for surface mount applications. With the DLS all that is required for installation is a 4/0 J-box. If there is already a housing in place, don't fret - the DLS is versatile enough for use in most 4" recessed housings. Upgrading to energy efficient LED lighting has never been easier, or more affordable. The DLS is dimmable to 10%, suitable for use in wet locations, and available in 2700K, 3000K, or 4000K color temperatures. The NICOR DLS provides superior efficacy and a longer life than compact fluorescents, with the pleasent light quality you expect from an incandescent lamp.

Easy surface mount installation into a plastic or metal 4/O J-box Compatible with most 4", 5", and 6" recessed housings (DLSS6 Only) Compatible with most 4" recessed housings (DLS4) Suitable for use in IC Rated recessed housings 50,000 hour life expectancy Greater than 90 CRI with R9 greater than 50 Meets California Quality Specifications Wet Location rated Dimmable to 10% with most standard dimmers Durable construction with integrated trim













DLS4

DLS56



5 Year Warranty



aesthetic appeal.

Compatible with most 5" and 6" recessed housings (DLG56 Only) Compatible with most 4" recessed housings (DLG4 Only) Suitable for use in IC Rated recessed housings 36,000 hour life expectancy Greater than 90 CRI with R9 greater than 50 Meets California Quality Specifications Easy installation with adjustable torsion springs (DLG56 Only) Easy installation with mounting clip system (DLG4 Only) Dimmable to 10% with most standard dimmers Durable construction with integrated trim 5 Year Warranty



















the flexibility for those applications where the standard DLR56 doesn't quite fit. With a 360°/30° range of motion the DEB56 gives you the ability to aim over 900 lumens exactly where it's needed.

Compatible with most 5" and 6" recessed housings Suitable for use in IC Rated recessed housings 36,000 hour life expectancy Greater than 90 CRI with R9 greater than 50 Meets California Quality Specifications Easy installation with adjustable torsion springs Dimmable to 10% with most standard dimmers Durable construction with integrated trim 5 Year Warranty















LED Downlight Square

Everything you love about the DLR4 is now available with the aesthetics of a square trim. Designed to boost energy efficiency, the LED light engine draws only 11 watts while achieving a light output to over 600 lumens. The enriched 90+ CRI light output provides superior color quality. Not only is the light quality better, but this design improvement meets new industry standards like Title 24.

Compatible with most 4" recessed housings Suitable for use in IC Rated recessed housings 36,000 hour life expectancy Greater than 90 CRI with R9 greater than 50 Meets California Quality Specifications Easy installation with mounting clip system Dimmable to 10% with most standard dimmers Durable construction with integrated trim 5 Year Warranty













DLQ4



D-Series

LED Downlight Family

Suitable for use in IC Rated recessed housings Greater than 90 CRI with R9greater than 50 Meets California Quality Specifications

Easy surface mount installation into a plastic or metal 4/O J-box (DLS4, DLS56 Only) Easy installation with mounting clip system (4" Fixtures Only)

Easy installation with adjustable torsion springs (DLR56, DLG56, DEB56 Only)

Dimmable to 10% with most standard dimmers

Durable construction with integrated trim

Energy Star Title 24

5 Year Warranty













DLG4 DLG56

DLG4 Ordering Information				Example: DLG4-10-120-3K-WH
Series	Version	Voltage	CCT's	Trim Color
DLG4	10 (1.0)	120	2K (2700)	WH (white)
			3K (3000)	
			4K (4000)	
DLG56	Ordering Info	Example: DLG56-10-120-3K-WH		
Series	Version	Voltage	CCT's	Trim Color
DLG56	10 (1.0)	120	2K (2700)	WH (white)
			3K (3000)	



DLR4 DLR56

DLR4 Ordering Information				Example: DLR4-27-120-3K-WH
Series	Version	Voltage	CCT's	Trim Color
DLR4	27 (2.7 600 lumen)	120	2K (2700)	BK (black)
			3K (3000)	NK (nickel)
			4K (4000)	OB (oil-rubbed bronze)
			5K (5000)	WH (white)
				WILL DE (coleita la effici. Accellata in 21, and c
				WH-BF (White barrie) Available in 3k only
DLR56	Ordering Info	rmatio	n	WH-BF (white baffle) Available in 3k only Example: DLR56-2709-120-3K-WH
DLR56 Series	Ordering Info	rmatio Voltage	n CCT's	
				Example: DLR56-2709-120-3K-WH
Series	Version	Voltage	CCT's	Example: DLR56-2709-120-3K-WH Trim Color
Series	Version 2709 (2.75 900lm)	Voltage	CCT's 2K (2700)	Example: DLR56-2709-120-3K-WH Trim Color BK (black)
Series	Version 2709 (2.75 900lm)	Voltage	2K (2700) 3K (3000)	Example: DLR56-2709-120-3K-WH Trim Color BK (black) NK (nickel)



|--|

DLS4 C	Ordering Infor	Example: DLS4-2006-120-3K-WH		
Series	Version	Voltage	CCT's	Trim Color
DLS4	2006 (2.0 600lm)	120	2K (2700)	WH (white)
			3K (3000)	
			4K (4000)	
DLS56	Ordering Info	rmatio	n	Example: DLS56-2009-120-3K-WH
DLS56 Series	Ordering Info	rmatio Voltage	n CCT's	Example: DLS56-2009-120-3K-WH Trim Color
				<u> </u>
Series	Version	Voltage	CCT's	Trim Color



DEB56

Ordering Information				Example: DEB56-20-120-3K-W
Series	Version	Voltage	CCT's	Trim Color
DEB56	20 (2.0)	120	2K (2700)	WH (white)
			3K (3000)	
			4K (4000)	



DLQ4

Orderi	ng Informati	Example: DLQ4-10-120-3K-WH		
Series	Version	Voltage	CCT's	Trim Color
DLQ4	10 (1.0)	120	2K (2700)	WH (white)
			3K (3000)	
			4K (4000)	



D-Series LED Downlight Family

Warehouse Locations

Albuquerque NM

Detroit MI

Miami FL

Syracuse NY

La Mirada CA

T 800.821.6283

F 800.892.8393

www.nicorlighting.com

2200 Midtown Place NE

Albuquerque NM 87107 USA

NICOR 2015 LED DOWNLIGHT FAMILY

